



# Town of York

186 York Street  
York, Maine 03909-1314

MAP \_\_\_\_ . LOT \_\_\_\_

Town Manager/  
Selectmen  
(207)363-1000

Town Clerk/  
Tax Collector  
(207)363-1003

Finance/  
Treasurer  
(207)363-1004

Code  
Enforcement/  
Planning  
(207)363-1002  
(207)363-1007

Assessor  
(207)363-1005

Police Department  
(207)363-1031

Dispatch  
(207)363-2557

York Beach Fire  
Department  
(207)363-1014

York Village Fire  
Department  
(207)363-1015

Public Works/  
Harbor Master  
(207)363-1010

Senior Center/  
General Assistance  
(207)363-1036

Parks and  
Recreation  
(207)363-1040

Grant House  
(207)351-1204

Fax  
(207)363-1009  
(207)363-1019

## ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES

### STABILIZED CONSTRUCTION ENTRANCE

Required

#### SPECIFICATIONS

1. **AGGREGATE SIZE** - Use 2" stone or reclaimed or recycled concrete equivalent.
2. **AGGREGATE THICKNESS** - Not less than six (6) inches.
3. **WIDTH** - 10' minimum, but not less than the full width of points where ingress or egress occurs.
4. **LENGTH** - As required, but not less than 50' (except on a single residence lot where a 30' minimum would apply).
5. **GEOTEXTILE** - To be placed over the entire area to be covered with aggregate. Filter cloth will not be required on a single family residence lot. Piping of surface water under entrance shall be provided as required. If piping is impossible, a mountable berm with 5:1 slopes will be permitted.
6. **CRITERIA FOR GEOTEXTILE** - The filter cloth shall be woven or non-woven fabric consisting only of continuous chain polymeric filaments or yards of polyester. The fabric shall be inert to commonly encountered chemicals, hydrocarbons, mildew, rot resistant, and conform to the fabric properties as shown:

See reverse side

\_\_\_\_\_  
Applicant's Signature

\_\_\_\_\_  
Date